

LP-740 & LP-1000

Low Profile RFID Tags

JetCorp Unisonic



ZM-4462

- Depend on Express RFID labels to deliver the performance you require for item-level tagging applications.
- Encoded, printed and ready to use for track and trace.
- Low Profile (.004" thick) enhances durability.

ADVANTAGES

- Permanent acrylic adhesive
- Low cost; high performance
- Tamper proof
- Broad-spectrum 860-960 MHz for world-wide deployment

Common Applications:

Logistics

Asset Tracking

Physical Specifications

Tag Dimensions	LP-704 2.91" x 0.8"
Attachment Method	LP-1000 3.94" x1.02"
Material	Pressure Sensitive Adhesive
	Polyester

RF Specifications

IC Type	Impinj Monza A R6-P
User Memory	61 bits
EPC Memory	128 bits
Operating Frequency	860-960 MHz
Read Range (Typical)	10 Feet
RF Protocol	EPC Class 1 Gen 2

Environmental Specifications

Durability	Medium Duty
Mounting Substrates	Plastic, Wood, Paperboard (not metal)

800.382.2323 (toll free)
858.549.9828

858.549.8708
Mail@ExpressCorp.com

9155 Trade Place, San Diego, CA 92126 | ExpressCorp.com

ISO 9001:2008 Certified - ITAR Registered
Member: Automatic Identification Manufacturers Association
Member: AIM UID Supplier Alliance
Member: National Assn. of Graphic Identification Product Manufacturers
Member: Specialty Graphic Imaging Association


EXPRESS
IDENTIFICATION MADE SIMPLE